


AUBO-i3

i Series Collaborative Robot



3 KG
PLAYLOAD



16.4 KG
WEIGHT



±0.02 mm
REPEATABILITY



625 mm
WORKING RADIUS

- ✓ Lightweight Design, Only 16.4 kg
- ✓ 3 kg payload, Up to 625 mm Reach
- ✓ Compact and Lightweight, Small Footprint

Applications

3C Electronics, Automotive, New Energy, Semiconductor, Machining, Hardware & Home Appliances, Kitchen & Bathroom Products, Healthcare, Education & Research, Food & Beverage, Retail, Daily Chemical, and Logistics



CERTIFICATIONS

- ISO 13849-1 (PL d, Category 3)
- CE Certification
- NRTL Certification
- KC Certification
- SEMI S2 Certification
- RoHS Certification
- Reach Certification
- ISO Class 4 Cleanroom Suitable



Features & Advantages

- 01 Higher Precision:** Enhanced repositioning and point-to-point accuracy, with reduced collision force thresholds and millisecond-level system response. Delivers more precise positioning and smoother motion trajectories
- 02 Faster Speed:** Operating speed increased by 10%–20%. The 6-axis robot enables more efficient operation and significantly improves productivity
- 03 Enhanced Functionality:** Open system architecture with integrated RS485 communication. Supports drag-to-teach functionality and external device power supply, enabling seamless communication with end-effectors, vision systems, mobile platforms, and other peripheral equipment for greater flexibility and easier integration
- 04 Improved Safety:** Certified to multiple international standards. Enhanced collision detection sensitivity ensures safe and reliable human-robot collaboration without the need for additional safety fencing



High Performance



High Precision



Fast Response



Flexible Production



Precision Machining



Safety and Stability




High Protection Grade




Compact Footprint




Modular Design




AUBO-i3 Dimensions Diagram



AUBO-i3 Point P Motion Range




AUBO-i3 End Flange



AUBO-i3 Base Top View

Specification

Degrees of Freedom	6
Max Working Radius	625 mm
Payload	3 kg
Weight	16.4 kg
Footprint Diameter	Ø140
Repeatability	±0.02
Tool Speed	≤2.5 m/s
Average Power	150 W
Peak Power	1000 W
Operating Temp. Range	0-50 °C
Operating Humidity	90% RH (Non-condensing)
Mounting	Any Angle
IP Classification	IP54



Joint Motion	Joint 1	Joint 2	Joint 3	Joint 4	Joint 5	Joint 6
Range of Motion	±360°	±360°	±156°	±360°	±360°	±360°
Max Speed	237 °/s	237 °/s	237 °/s	237 °/s	237 °/s	237 °/s

*Joint motion capabilities may be limited by application scenarios; maximum speeds may not be reached. Please note this during use.

Control Cabinet

Product Model	AUBO-CB-iS	
Dimension (L*W*H)	400 mm*160 mm*320 mm	
Weight	12.5 kg	
Robot Arm Cable Length	5 m (Customizable, up to 8 m)	
Teach Pendant Cable Length	4 m	
Power Cable Length	5 m	
Communication Protocols	Ethernet, ModBus-RTU/TCP, Profinet Ethernet/IP (Optional)	
Interfaces & Openness	SDK (C/C++/C#/Lua/Python/JavaScript Windows + Linux) Supporting ROS/ROS2, AP	
Power Supply	115/230VAC, 50/60Hz	
IP Classification	IP43	



I/O Interfaces		Control Cabinet	Tool End
I/O Interfaces	Digital Input	16 (Standard), 16 (Configurable) / 8 (Safety)	4 (Configurable)
	Digital Output	16 (Standard), 16 (Configurable) / 8 (Safety)	4 (Configurable)
	Analog Input	2	2
	Analog Output	2	-
	485 Communication	2	1 (Optional)
I/O Power	Output Voltage	24 V	0V/12V/24V
	Output Current	3A Max	2A (3A Max)

Teach Pendnat

Product Model	AUBO-TP-IS
Dimension (L*W*H)	254 mm*213.1 mm*40.8 mm
Weight	1.0 kg
IP Classification	IP54
Color	Orange + Black



Disclaimer:

1. The contents of this product brochure are subject to change without prior notice.

2. This product brochure is copyrighted by the company. Any reproduction or quotation of its contents must clearly indicate the source. Unauthorized reproduction or distribution without permission may be considered infringement, and legal responsibility will be pursued in accordance with applicable laws.

Revision Date: June 16th, 2026

